

# Growatt 3000~6000TL3-S

- Max. Efficiency 98.4%
- Dual MPP trackers
- Supports export limitation
- Integrated DC switch
- Max.DC voltage 1000VDC
- Natural cooling



P O W E R  
- I N G O  
T O M O -  
R R O W O

Datasheet	3000TL3-S	4000TL3-S	5000TL3-S	6000TL3-S
-----------	-----------	-----------	-----------	-----------

### Input Data

Max. recommended PV power (for module STC)	3999W	5320W	6650W	7980W
Max. DC voltage	1000V	1000V	1000V	1000V
Start Voltage	140V	140V	140V	140V
MPP work voltage range	160V-1000V	200V-1000V	200V-1000V	200V-1000V
Nominal voltage	620V	620V	620V	620V
Max. input current	11A/11A	11A/11A	11A/11A	11A/11A
Number of independent MPP trackers/strings per MPP tracker	2/1	2/1	2/1	2/1

### Output (AC)

Rated AC output power	3000W	4000W	5000W	6000W
Max. AC apparent power	3000VA	4000VA	5000VA	6000VA
Max. output current	5.1A	6.8A	8.5A	10.2A
AC nominal voltage	230V/400V ; 320-478V	230V/400V ; 320-478V	230V/400V ; 320-478V	230V/400V ; 320-478V
AC grid frequency	50Hz/60Hz, ±5Hz	50Hz/60Hz, ±5Hz	50Hz/60Hz, ±5Hz	50Hz/60Hz, ±5Hz
Power factor	0.8leading - 0.8lagging	0.8leading - 0.8lagging	0.8leading - 0.8lagging	0.8leading - 0.8lagging
THDI	<3%	<3%	<3%	<3%
AC grid connection type	3W+N+PE	3W+N+PE	3W+N+PE	3W+N+PE

### Efficiency

Max. efficiency	97.5%	97.8%	98.0%	98.0%
Euro - eta	96.5%	96.7%	96.9%	97.1%
MPPT efficiency	99.5%	99.5%	99.5%	99.5%

### Protection Devices

DC reverse polarity protection	yes	yes	yes	yes
DC switch	yes	yes	yes	yes
Output over current protection	yes	yes	yes	yes
Output AC overvoltage Protection - Varistor	yes	yes	yes	yes
Ground fault monitoring	yes	yes	yes	yes
Grid monitoring	yes	yes	yes	yes
Integrated all-pole sensitive leakage current monitoring unit	yes	yes	yes	yes

### General Data

Dimensions (W / H / D) in mm	480/448/200	480/448/200	480/448/200	480/448/200
Weight	21.2kg	21.2kg	21.2kg	21.2kg
Operating temperature range	-25 °C ... +60 °C	-25 °C ... +60 °C	-25 °C ... +60 °C	-25 °C ... +60 °C
Noise emission (typical)	≤35 dB(A)	≤35 dB(A)	≤35 dB(A)	≤35 dB(A)
Altitude	3000m	3000m	3000m	3000m
Self-consumption night	< 0.5W	< 0.5W	< 0.5W	< 0.5W
Topology	Transformerless	Transformerless	Transformerless	Transformerless
Cooling concept	Natural	Natural	Natural	Natural
Environmental Protection Rating	IP65	IP65	IP65	IP65
Relative humidity	0~100%	0~100%	0~100%	0~100%

### Features

DC connection	H4/MC4(opt)	H4/MC4(opt)	H4/MC4(opt)	H4/MC4(opt)
AC connection	Connector	Connector	Connector	Connector
Display	LCD	LCD	LCD	LCD
Interfaces:RS232/RS485/RF/Ethernet/Wi-Fi	yes/yes/opt/opt/opt	yes/yes/opt/opt/opt	yes/yes/opt/opt/opt	yes/yes/opt/opt/opt
Warranty:5 years/10 years	yes/opt	yes/opt	yes/opt	yes/opt